



1 MANUAL OVER-RIDE HANDWHEEL PROVIDED ONLY ON ACTUATORS ER-4-10-4, ER-6-15-4 AND ER-10-15-4 (ON TOP).

SIZE	ACTUATOR	DIMENSIONS (INCHES)							WT.(LBS)
		A	B	C	D	E	F	G	
1/4", 3/8"	ER-2-5-4	2.68	8.44	6.88	4.25	0.63	1.34	3.0	12
1/2"	ER-2-5-4	2.95	8.58	6.88	4.25	0.74	1.48	3.0	12
3/4"	ER-2-5-4	3.39	8.83	6.88	4.25	0.94	1.69	3.0	15
1"	ER-4-10-4	4.06	10.25	6.88	4.25	1.10	2.03	4.0	23
1 1/4"	ER-6-15-4	4.53	10.41	6.88	4.25	1.26	2.26	4.0	24
1 1/2"	ER-6-15-4	4.92	10.83	7.00	7.00	1.53	2.46	4.0	25
2"	ER-10-15-4	5.75	11.18	7.00	7.00	1.88	2.87	4.0	33

MAX. DIFF. PRESSURE ACROSS VALVE
 SEAT MATERIAL-RPTFE
 DIMENSIONS GIVEN FOR NEMA 4 ENCLOSURE

TOL. UNLESS OTHERWISE NOTED (IN.)
 VA. END-TO-END LENGTH: ± 1/16"
 OTHER VA. DIM.: ≤NPS 2", ± 1/8";
 NPS 2 1/2"-4", ± 1/4"; >4", ± 1/2"
 VA.-ACT. ASSY & PIPING DIM.: ± 1/2"

CUSTOMER ORDER # _____
 CUSTOMER _____
 TAG No. _____
 SIZE & MODEL # 1/4"-2" 3T-3700R/3L-3800R
 RED. PORT W/ELECTRIC ACUATOR, FNPT/FSW ENDS
 CERTIFIED _____ DATE _____

 **MARWINVALVE**
 a division of Richards Industries
 CINCINNATI, OHIO U.S.A
 www.marwinvalve.com

DR. BY	DW	05/03/11	MD03008
CHK.BY			