



SIZE	ACTUATOR	DIMENSIONS (INCHES)											WT (LBS)
		A	B	C	D	E	F	G	H	J	K	L	
1/4" & 3/8"	UT-0-DA	2.68	6.59	5.5	2.8	0.63	1.06	1.34	2.74	0.79	1.6	2.00	9.2
	UT-1-SR		7.02	6.4	3.2				3.17	0.79	1.8		13.8
1/2"	UT-0-DA	2.95	6.73	5.5	2.8	0.74	1.20	1.48	2.74	0.79	1.6	2.00	9.2
	UT-2-SR		7.81	8.2	3.7				3.82	0.79	2.1		16.7
3/4"	UT-1-DA	3.39	7.41	6.4	3.2	0.94	1.45	1.69	3.17	0.79	1.8	2.00	11.2
	UT-2-SR		8.06	8.2	3.7				3.82	0.79	2.1		17.3
1"	UT-2-DA	4.08	8.16	8.2	3.7	1.10	1.55	2.03	3.82	0.79	2.1	2.00	15.5
	UT-3-SR		9.12	10.7	4.8				4.78	0.79	2.7		23.5
1 1/4"	UT-2-DA	4.53	8.32	8.2	3.7	1.26	1.71	2.26	3.82	0.79	2.1	2.00	15.8
	UT-3-SR		9.28	10.7	4.8				4.78	0.79	2.7		24.6
1 1/2"	UT-2-DA	4.92	8.74	8.2	3.7	1.53	2.13	2.46	3.82	0.79	2.1	2.00	17.8
	UT-3.5-SR		10.88	12.9	5.4				5.57	1.18	2.9		32.2
2"	UT-2.5-DA	5.75	9.51	9.4	4.2	1.88	2.48	2.87	4.27	0.79	2.3	2.00	28.2
	UT-3.5-SR		11.23	12.9	5.4				5.57	1.18	2.9		33.5

MAX. DIFF. PRESSURE ACROSS VALVE
SEAT MATERIAL-RPTFE

TOL. UNLESS OTHERWISE NOTED (IN.)

VA. END-TO-END LENGTH: ± 1/16"
OTHER VA. DIM.: ≤NPS 2", ± 1/8";
NPS 2 1/2"~4", ± 1/4"; >4", ± 1/2"
VA.-ACT. ASSY & PIPING DIM.: ± 1/2"

CUSTOMER ORDER # _____
CUSTOMER _____
TAG No. _____
SIZE & MODEL # 1/4"-2" 3T-37R/3L-38R
RED. PORT W/UT (NEW STYLE) ACT, @80PSI PRES.
CERTIFIED _____ DATE _____

 **MARWINVALVE**
a division of Richards Industries
CINCINNATI, OHIO U.S.A
www.marwinvalve.com

DR. BY DW 02/02/11
CHK. BY

MD03093