



SIZE	ACTUATOR	DIMENSIONS (INCHES)										WT (LBS)
		A	B	C	D	E	F	G	H	J	K	
1/4"	UT-0A-DA	2.63	3.76	4.3	1.8	0.67	1.20	1.31	1.77	0.79	0.9	2
	UT-0-SR		4.73	5.5	2.8				2.74	0.79	1.6	4
3/8"	UT-0A-DA	2.63	3.76	4.3	1.8	0.67	1.20	1.31	1.77	0.79	0.9	2
	UT-0-SR		4.73	5.5	2.8				2.74	0.79	1.6	4
1/2"	UT-0A-DA	2.87	3.76	4.3	1.8	0.67	1.20	1.43	1.77	0.79	0.9	2
	UT-0-SR		4.73	5.5	2.8				2.74	0.79	1.6	4
3/4"	UT-0A-DA	3.18	3.84	4.3	1.8	0.80	1.28	1.59	1.77	0.79	0.9	3
	UT-0-SR		4.81	5.5	2.8				2.74	0.79	1.6	5
1"	UT-1-DA	3.74	5.59	6.4	3.2	0.94	1.63	1.87	3.17	0.79	1.8	7
	UT-2-SR		6.24	8.2	3.7				3.82	0.79	2.1	11
1 1/4"	UT-1-DA	4.38	5.81	6.4	3.2	1.18	1.85	2.20	3.17	0.79	1.8	9
	UT-2-SR		6.46	8.2	3.7				3.82	0.79	2.1	13
1 1/2"	UT-1-DA	4.86	6.30	6.4	3.2	1.42	2.34	2.43	3.17	0.79	1.8	12
	UT-2-SR		6.95	8.2	3.7				3.82	0.79	2.1	15
2"	UT-2-DA	5.70	7.51	8.2	3.7	1.69	2.90	2.86	3.82	0.79	2.1	23
	UT-3-SR		8.47	10.7	4.8				4.78	0.79	2.7	32

MAX. DIFF. PRESSURE ACROSS VALVE

SEAT MATERIAL-RPTFE

TOL. UNLESS OTHERWISE NOTED (IN.)

VA. END-TO-END LENGTH: ± 1/16"
 OTHER VA. DIM.: ≤NPS 2", ± 1/8";
 NPS 2 1/2"-4", ± 1/4"; >4", ± 1/2"
 VA.-ACT. ASSY & PIPING DIM.: ± 1/2"

CUSTOMER ORDER # _____

CUSTOMER _____

TAG No. _____

SIZE & MODEL # 1/4"-2" REDUCED PORT 3T-33R/
3L34R W/UT (NEW STYLE) ACT, @80PSI PRESSURE

CERTIFIED _____ DATE _____



a division of Richards Industries

CINCINNATI, OHIO U.S.A

www.marwinvalve.com

DR. BY	DW	02/02/11
CHK. BY		

MD03092